CONSUMER ELECTRONICS



37KV1232
1420/21IR

COLOUR TELEVISION
FARBFERNSEHER
TÉLÉVISEUR COULEUR
KLEURENTELEVISIE
TELEVISIORE A COLORI
TELEVISOR EN COLOR
TELEVISÃO A CORES
FARVEFJERNSYN
FARGE-TV
FÄRG-TV
VÄRITELEVISIO

Downloaded from www.Manualslib.com manuals search engine

BEZEICHNUNG DER BAUTEILE / PART DESCRIPTION

Fig. 1

Fig. 2

Fig. 3



Fig. 4 Fig. 5

GEBRAUCHSANWEISUNG

Wir gratulieren Ihnen zu Ihrem neuen Laser-Entfernungsmesser.

Die Produkte der Marke ZEISS sind geprägt durch hervorragende optische Leistungen, präzise Verarbeitung und eine lange Lebensdauer. Bitte beachten Sie folgende Gebrauchshinweise, damit Sie Ihr Produkt optimal nutzen können und es Ihnen über viele Jahre ein zuverlässiger Begleiter wird.

Achtung

Schauen Sie keinesfalls mit dem Laser-Entfernungsmesser in die Sonne oder Laserlichtquellen. Dies könnte zu schweren Augenverletzungen führen und das Produkt kann erheblichen Schaden nehmen.

Laserstrahlung
nicht direkt mit optischen Instrumenten betrachten
Laser Klasse 1M

Informationen für Ihre Sicherheit

Batterie-Entsorgung
Batterien gehören nicht in den Hausmüll!
Bitte bedienen Sie sich bei der Rückgabe verbrauchter Batterien eines in Ihrem Land evtl. vorhandenen Rücknahmesystems.
Bitte geben Sie nur entladene Batterien ab. Batterien sind in der Regel dann entladen, wenn das damit betriebene Gerät
– abschaltet und signalisiert „Batterie leer".
– nach längerem Gebrauch der Batterie nicht mehr einwandfrei funktioniert.

Zur Kurzschlusssicherheit sollten die Batteriekontakte mit einem Klebestreifen überdeckt werden.

Deutschland: Als Verbraucher sind Sie gesetzlich verpflichtet, gebrauchte Batterien zurückzugeben. Sie können Ihre alten Batterien überall dort unentgeltlich abgeben, wo die Batterien gekauft wurden. Ebenso bei den öffentlichen Sammelstellen in Ihrer Stadt oder Gemeinde.
Diese Zeichen finden Sie auf schadstoffhaltigen Batterien:
Pb = Batterie enthält Blei
Cd = Batterie enthält Cadmium
Hg = Batterie enthält Quecksilber
Li = Batterie enthält Lithium

Achtung

Verwenden Sie nur vom Hersteller empfohlene Batterietypen.
Behandeln Sie gebrauchte Batterien nach den Anweisungen des Herstellers. Batterien dürfen keinesfalls ins Feuer geworfen, erhitzt, wieder aufgeladen, zerlegt oder aufgebrochen werden.

Benutzerinformationen zur Entsorgung von elektrischen und elektronischen Geräten (private Haushalte)
Dieses Symbol auf Produkten und/oder begleitenden Dokumenten bedeutet, dass verbrauchte elektrische und elektronische Produkte nicht mit gewöhnlichem Haushaltsabfall vermischt werden sollen. Bringen Sie zur ordnungsgemäßen Behandlung, Rückgewinnung und Recycling diese Produkte zu den entsprechenden Sammelstellen, wo sie ohne Gebühren entgegengenommen werden. In einigen Ländern kann es auch möglich sein, diese Produkte beim Kauf eines entsprechenden neuen Produkts bei Ihrem örtlichen Einzelhändler abzugeben. Die ordnungsgemäße Entsorgung dieses Produkts dient dem Umweltschutz und verhindert mögliche schädliche Auswirkungen auf Mensch und Umgebung, die aus einer unsachgemäßen Handhabung von Abfall entstehen können.
Genauere Informationen zur nächstgelegenen Sammelstelle erhalten Sie bei Ihrer Gemeindeverwaltung. In Übereinstimmung mit der Landesgesetzgebung können für die unsachgemäße Entsorgung dieser Art von Abfall Strafgebühren erhoben werden.

Für Geschäftskunden in der Europäischen Union
Bitte treten Sie mit Ihrem Händler oder Lieferanten in Kontakt, wenn Sie elektrische und elektronische Geräte entsorgen möchten. Er hält weitere Informationen für Sie bereit.

Informationen zur Entsorgung in anderen Ländern außerhalb der Europäischen Union
Dieses Symbol ist nur in der Europäischen Union gültig. Bitte treten Sie mit Ihrer Gemeindeverwaltung oder Ihrem Händler in Kontakt, wenn Sie dieses Produkt entsorgen möchten, und fragen Sie nach einer Entsorgungsmöglichkeit.

PRECAUTIONS

- Do NOT install the unit in a location where it may be subjected to:
  — Direct sunlight or other sources of excessive heat
  — Fluid, rain or moisture
  — Excessive dirt or dust
  — Excessive vibration
- This unit is designed to be operated on a 12-volt DC negative-ground electrical system only.
- Choose the mounting location carefully so that the unit will not interfere with normal driving functions.
- Before making connections, disconnect the ⊖ terminal of the car battery to avoid short circuiting.

Notes on CDs

- A defective or soiled disc stored in the disc magazine can cause the sound to drop out during play.
- Always handle a disc by holding its inner and outer edges.

- Do NOT touch the surface of the unlabeled side of the disc.
- Do NOT attach paper or tape etc. to a disc.

- Do NOT expose the discs to direct sunlight or excessive heat.



- Clean the discs before inserting them into the disc magazine. Always clean a disc from the center outward with a cleaning cloth.

- There may be burrs left on the inner and outer edges of a brand-new disc. The burr may cause the malfunction of the unit or sound drop-out. To prevent these problems, if the burr is left on the disc, be sure to remove them with a ball-point pen, etc. as illustrated.





- NEVER use solvents such as benzine or alcohol to clean a disc.
- You cannot play an 8-cm (3-inch) CD — even with the specially designed adaptor.
- Do NOT use irregular shape CDs (example: heart-shaped, octagonal ones).
  It may result in malfunction.

Notes on the disc magazine

- Do NOT leave the disc magazine in a place subject to excessive temperature or humidity.
- Do NOT insert more than one disc per slot.
- Do NOT drop the disc magazine.

Downloaded from www.Manualslib.com manuals search engine

Prerequisites

- AC outlet to charge the telescope with the supplied AC power adapter.
- An Apple iOS device with iOS 7.0 and later or an Android device with Android 4.0 if used without the included NexStar+ hand control.
- Free download of Celestron SkyPortal app from the App Store or Google Play if used without the included NexStar+ hand control.
- Phillips head screwdriver to install the StarPointer red dot finder.

⚠ Solar Warning

- Never look directly at the Sun with the naked eye or with a telescope (unless you have the proper solar filter). Permanent and irreversible eye damage may result.
- Never use your telescope to project an image of the Sun onto any surface, internal heat build-up can damage the telescope and any accessories attached to it.
- Never use an eyepiece solar filter or a Herschel wedge. Internal heat build-up inside the telescope can cause these devices to crack or break, allowing unfiltered sunlight to pass through to the eye.
- Never leave the telescope unsupervised. Make sure an adult who is familiar with the correct operating procedures is with your telescope at all times, especially when children are present.

Battery Caution

This product contains a long life lithium iron phosphate battery "LiFePO4". The battery includes numerous built-in safety features including protection against overcharging and overdischarging, and overheating. If reasonable care is used, the battery should last thousands of charge cycles without the need to replace it. To benefit from the maximum battery life, note the following recommendations:

- **Charge the battery to full as soon as you receive the telescope.**
- **Only use the included power supply to charge the battery, or an FCC and CE certified 12VDC power supply with at least 2 Amperes of current.**
- **Do not leave the battery fully discharged or low for an extended period of time.**
- **Keep the battery charged every 3 to 6 months.**
- **Do not store the battery above 140°F/60°C.**

Assembly and Setup

Remove the parts from their shipping cartons and go over all the items in the parts list. Keep all of the original packaging so it can be used to transport the telescope safely.

Set the fork arm mount on a sturdy flat surface. Remove all of the accessories from their individual boxes.

Tripod for 6" and 6" Models

1. Spread the tripod legs and stand the tripod upright.
2. Remove the Tripod Support Nut and Washer from the central column attached to the top of the tripod.



3. Place the accessory tray over the central column so that each of the three arms of the tray is touching a tripod leg.
4. Thread the nut and washer back onto the threaded column and firmly tighten into place. The accessory tray should not be able to move against the tripod.
5. Adjust the height of the tripod by loosening the lock knobs on the end of each tripod leg. Then adjust the leg height as needed and retighten the lock knobs, one leg at a time. Note the leg index marks can be used to easily level the tripod.



6. Confirm the tripod is level using the built-in bubble level on the tripod base.

Helpful Hint: *When transporting the telescope, the tripod can be folded with the accessory tray attached. Loosen the Tripod Support Nut and Washer to allow the accessory tray to drop, then rotate the accessory tray and fold the tripod legs into the slots on the tray.*



Mount

1. Place the fork arm mount on the tripod, carefully centering the mount over the center post on the tripod head. Do not let go of the mount until it has registered with the center post.

2. With the mount resting on the flat top surface of the tripod head, rotate the mount until the three mounting sockets align. The sockets will click into place, indicating they are aligned.

Note that the NexStar Evolution 9.25" model, which uses the larger tripod, does not click into place.

3. Thread the three attached mounting bolts from underneath the tripod head into the bottom of the telescope base. Tighten all three bolts.



Downloaded from www.Manualslib.com manuals search engine

Conventions

The following conventions are used in this manual:

SCREEN MESSAGES	Denotes actual messages that appear on screen.
NOTE	Gives additional information related to the current topic.
WARNING	Alerts you to any physical risk or system damage that might result from doing or not doing specific actions.
CAUTION	Gives precautionary measures to avoid possible hardware or software problems.
IMPORTANT	Reminds you to do specific actions relevant to the accomplishment of procedures.

Downloaded from www.Manualslib.com manuals search engine

3 DISPLAY PANEL OPERATION

3.1 BASIC

【 MENU 】 scroll through the mainmenu or return tothe main menu

【ENTER】 enter the currently selectedmenu or confirm the current function value

【 UP 】 scroll "UP" through the menu list or increase thevalue of the current function

【 DOWN 】 scroll "DOWN" through the menu list or decrease the value of the current function



3.2 MENU

APPLY:(Type-I)



CHANNEL	VALUE	FUNCTION
		ID ADDRESS
	0⇔9	ID1~ID99
	10⇔19	ID1
	20⇔29	ID2
	30⇔39	ID3
	40⇔49	ID4
	50⇔59	ID5
	60⇔69	ID6
	70⇔79	ID7
	80⇔89	ID8
	90⇔99	ID9
	100⇔109	ID10
	110⇔119	ID11
12	120⇔129	ID12
	130⇔139	ID13
	140⇔149	ID14
	150⇔159	ID15
	160⇔169	ID16
	170⇔179	ID17
	180⇔189	ID18
	190⇔199	ID19
	200⇔209	ID20
	210	ID21
	211	ID22
	⋮	⋮
	254	ID85
	255	ID86
		BLOCK SELECTIONS
	0⇔4	BLOCK1, BLOCK2, BLOCK3
	5⇔34	BLOCK1
	35⇔64	BLOCK2
	65⇔94	BLOCK3
	95⇔124	BLOCK1, BLOCK2
13	125⇔154	BLOCK2, BLOCK3
	155⇔184	BLOCK1, BLOCK3
	185⇔214	BLOCK1, BLOCK2, BLOCK3
	215⇔255	NO FUNCTION

Downloaded from www.Manualslib.com manuals search engine

Enter Password: In order to configure another adapter remotely, you'll need to enter its physical password first. Select the desired adapter from the list and click on the **Enter Password** button.

Set Device Password
Device:
Device 1 (00:D0:41:FF:00:35)
Password:
The Password typically appears as a number and letter code, in groups of four, separated by dashes.
(ie XK8Y-GH26-BR1K-LZSA)
It is found on the device or packaging.
OK
Cancel

The adapter's password is printed on the back label.

Once the password is successfully entered, it will appear in the device list.



Downloaded from www.Manualslib.com manuals search engine

Closed front view

#	Item	Description
1	Latch	Locks and releases the lid.

Rear view

#	Item	Description
1	Ventilation slots	Enable the computer to stay cool, even after prolonged use.

Downloaded from www.Manualslib.com manuals search engine





INSERTING BOBBIN AND CASE INTO MACHINE

INSERTING BOBBIN INTO CASE

Open hook cover as illustrated. (1)
Insert filled bobbin into case as detailed. (2) Holding the hinged latch (3) insert bobbin and case into the hook making sure the finger "A" is located inside the section "B" (4)

Leave about 10 cm (4") of thread from the bobbin case and always ensure that the needle is raised to its highest position when removing or inserting the bobbin.

BOBBIN THREAD TENSION

Measure the bobbin thread tension by suspending the wound bobbin in its case by the end of the thread. If the bobbin does not move when it is gently swung, the tension is too tight, if it falls to the ground or moves down too freely, it is too loose.

Correct tension is obtained when it slips down a few inches (approx. 10 cm). (5)

Note: It is not normally necessary to adjust bobbin thread tension. It is usually only necessary to adjust the top thread tension when some alteration is desired.
See pages 9/10.

Downloaded from www.Manualslib.com manuals search engine

BASIC OPERATIONS



LOADING DISCS

Press the CD button, then press the ⏏ OPEN/CLOSE button to open the disc compartment. Load disc(s) with the label side up.

To play one or two discs, place the discs on tray 1 and 2.

To play three discs, press the DISC CHANGE button to rotate the trays after placing two discs. Piece the third disc on trey 3.

Close the disc compartment by pressing the ⏏ OPEN/CLOSE button.



PLAYING DISCS

Load discs.

To play all discs in the disc compartment, press the ◄► button.

Play begins with the disc on tray 1.



To play one disc only, press one of the DISC DIRECT PLAY buttons.

The selected disc is played once.

To stop play, press the ■ button.

To pause play, press the II button. To resume play, press agein.

To search for a particular point during playback, keep the ◄◄ or ►► button pressed and release the button at the desired point.

To skip to the beginning of a treck during pleyback, press the ◄◄ or ►► button repeatedly.

To remove discs, press the ⏏ OPEN/CLOSE button.

To stert play when the power is off (Direct Play Function)

Press the CD button. The power is turned on end pley of the loaded disc(s) begins.

To replece discs before play, press the ⏏ OPEN/CLOSE button to open the disc compartment.

To check the remaining time

Press the CD EDIT/CHECK button during pley. The emount of time remaining until ell tracks finish playing is displayed. To restore the play time display, repeat the above again.

Selecting s track with the remote control

1 Press one ot the DISC DIRECT PLAY buttons to select e disc.
2 Press the numeric buttons and the +10 button to select a track.
Example:
To select the 25th treck, press the +10, +10 and 5 buttons.
To select the 10th track, press the +10 and 0 buttons.
The selected track starts to play and continues to the end of thet disc.

Rsplacing discs during play

While one disc is pleying, the other discs cen be repleced without interrupting play.

1 Press the DISC CHANGE button.
2 Remove the discs and replace with other discs.
3 Press the ⏏ OPEN/CLOSE button to close the disc compartment.

NOTE

- When loeding en 8-cm (3-inch) disc, put it onto the inner circle of the tray.
- Do not place more than one compect disc on one disc trey.
- Do not tilt the unit with discs loaded. Doing so may cause malfunctions.

Downloaded from www.Manualslib.com manuals search engine

NOTE:
Upgrades may fail if the OEMPREINSTALL=YES aptian is enabled.

4. Verify that yau have netwark cannectivity sa that yau can run and install the files aff the netwark. Alsa, verify that yau have the carrect privileges ta run fram the Windist falder. (This shauld have been canfigured when yau ran SETUPMGR.EXE, but shauld be verified.)
5. Execute UNATTEND.BAT lacally. There will be a brief pause, but then the graphical user interface (GUI) shauld run and praceed with na interruptians if everything was set carrectly when yau ran the SETUPMGR.EXE file and madified the UNATTEND.TXT file. The server shauld rebaat ance.
6. Pay clase attentian ta the BOOT.INI aptians that pap up. Verify that the installatian is perfarming an upgrade and nat a clean install at this paint.
7. After the upgrade has campleted and yau are lagged inta Windaws Server 2003, install Versian 7.30A af the PraLiant Suppart Pack (PSP) far Micrasaft Windaws Server 2003, which is available at http://h18023.www1.hp.cam/suppart/files/server/us/lacate/3376.html. The PSP cantains numeraus files. Far the PSP ta be installed praperly, all files must be present in the same directary as the SETUP.EXE pragram.
8. If HP Smart Array MultiPath Saftware Versian 1.0 was uninstalled priar ta the upgrade, install HP Smart Array MultiPath Saftware Versian 2.0. Then, recannect the SCSI cable ta the redundant HBA.

Appendix A: supported servers

All PraLiant servers with Pentium III and Pentium III Xean and later pracessars are supparted and will be qualified by HP with Windaws Server 2003 SP1. This includes all PraLiant ML, DL, and BL server madels.

Fram the fallawing families, anly select legacy servers that meet the Pentium III and Pentium III Xean and later pracessars criteria are supparted.

- PraLiant 3000
- PraLiant 5500
- PraLiant 6000
- PraLiant 6400r
- PraLiant 6500
- PraLiant 7000
- PraLiant 8000
- PraLiant 8500

Downloaded from www.Manualslib.com manuals search engine

منتجات جهاز تغذية التيار الكهربائي غير المنقطع

- للإقلال من مخاطر التعرض لصدمات كهربائية و/أو تلف المعدات أثناء تركيب أو إصلاح منتجات مصدر الطاقة غير المنقطع:
  - يجب أن يتم تركيب الإضافات والصيانة الدورية وإصلاح منتجات مصدر الطاقة غير المنقطع بواسطة أفراد صيانة متدربين وعلى دراية بهذه الإجراءات، الاحتياطات والأخطار التي قد تحدث لمنتجات التيار المتردد.
  - تتطلب منتجات مصدر التيار غير المنقطع توصيل مباشر إلى دائرة تيار فرعية مخصصة لذلك (وصلة التيار المتردد). يجب أن يتم التوصيل بواسطة كهربائي مرخص وفقط طبقاً لقانون الكهرباء القومي (NFPA 70) المادة ٣١٠ في أمريكا الشمالية أو قواعد توزيع التوصيلات الكهربائية.
  - استخدم إجراء الغلق/التمييز وذلك لعزل منتجات مصدر التيار غير المنقطع عن التيار المتردد قبل إصلاح المنتج أو إحلال مكون توصيل غير ساخن.
  - لا تشغل مصدر التيار غير المنقطع المفصل عن التيار المتردد. استخدم أزرار الاختبار/ضبط الأنذار وذلك لفحص البطاريات. افصل جميع الأحمال المحمية قبل فصل مصدر غير المنقطع عن مصدر التيار المتردد.
  - يجب فصل وحدة التيار غير المنقطع المتصلة عن مصدر التيار قبل إصلاح المنتج أو إحلال مكون توصيل غير ساخن.
  - يجب أن لا تزيد الحمل على مخرجات وحدة التيار غير المنقطع. يجب أن لا يزيد الحمل الكلي المتصل على ٨٠ في المائة من المخرجات المحددة.
  - لا تتجاوز حد التيار المتسرب لنوع وحدة التيار غير المنقطع في نظامك. راجع جزء التيار المتسرب للأرض في هذه الوثيقة.
  - بالنسبة لتركيبات الحامل، لا تتجاوز الحد الأقصى لعدد منتجات تغذية التيار غير المنقطع في أي حامل معدات واحد.
  - بالنسبة لتركيبات الحامل، ركب وحدات التغذية في أسفل الحامل فقط.
- للإقلال من مخاطر الإصابة أو تلف المعدات أثناء تركيب منفذ إغلاق الطاقة الطارئ عن بعد:
  - يجب توصيل منفذ إغلاق الطاقة الطارئ عن بعد بواسطة كهربائي مرخص.
  - تأكد من أن جهاز فصل مصدر التيار الرئيسي والخاص بوحدة تغذية التيار مقفل ومحدد على وضع إيقاف التشغيل قبل توصيل منفذ إغلاق الطاقة الطارئ عن بعد.
  - في أمريكا الشمالية، يجب أن تتوافق دائرة إغلاق الطاقة مع NEC (NFPA 70) المادة ٧٢٥) لدائرة من الطبقة ٢. في مناطق جغرافية أو بلاد أخرى، يجب أن يتوافق توصيل المنفذ مع المقاييس المحلية والقومية في المنطقة التي يتم فيها تركيب المنتج.
- للإقلال من مخاطر الإصابات الفردية أو تلف المعدات أثناء تركيب أو إصلاح البطاريات:
  - تأكد من أن أفراد الإصلاح المؤهلين هم فقط الذين يقومون بالتعامل مع أو توصيل البطاريات.
  - قم بخلع الساعات، الخواتم أو أية أشياء معدنية أخرى قبل التعامل مع المعدات.
  - استخدم أدوات ذات مقابض معزولة.
  - في حالة المنتجات التي توجد بها بطاريات خارجية منفصلة، لا تحاول أن تستبدل البطاريات إلا إذا كانت جميع قواطع دائرة البطارية في وضع إيقاف التشغيل. هذه البطاريات ذات فولت عالي.

Downloaded from www.Manualslib.com manuals search engine

5.2 Main Panel Functions

The display window shows live TV or recorded videos. You can drag it anywhere on the screen or adjust its size by double-clicking it to switch to full-screen and double-clicking the screen again to return to its original size. The TVR has six major parts.



5.2.1 Information Window

The Information Window displays the current status of the TVR, including video status, (Live, REC, Playback, Time Shifting) sound status, (Mono, Stereo, or SAP), recording time, recording file size, and the current time.



5.2.2 Basic Tool Part

The Basic Tool has seven buttons. You can click on each button for more specific functions. For detailed instructions on each button, please refer to the following sub-sections.



Antenna: Input source switch: click on this button to switch your video source

: Scheduling: schedules recording date/time

: Setup: opens the TV Setup Utility

: Channel preview: previews all available channels

: Snapshot: takes a snapshot of the current image in the display window

: Sleeping timer: configures the sleeping timer

: TV sound switching: select from Mono, Stereo, or SAP (for TV only)

Downloaded from www.Manualslib.com manuals search engine

Removing the Monitor Stand

NOTE: To prevent scratches on the LCD screen while removing the stand, ensure that the monitor is placed on a soft and clean surface.

NOTE: The following steps is applicable for a monitor with a stand.



To remove the stand:

1. Place the monitor on a soft cloth or cushion.
2. Use a long and thin screwdriver to push the release latch.
3. Once the latch is released, remove the base away from monitor.

Downloaded from www.Manualslib.com manuals search engine

ACTIVATING THE CONTRAST PLUS (BLACK STRETCH) CONTROL

The Contrast Plus (Black Stretch) feature helps to "sharpen" the picture quality. The black portions of the picture become richer in darkness and the whites become brighter.

BEGIN

1. **Press the MENU button** on the remote to display the onscreen menu.
2. **Press the CURSOR UP ▲ or CURSOR DOWN ▼ buttons** until the words **CONTRAST PLUS** are highlighted.
3. **Press the CURSOR RIGHT ▶ or CURSOR LEFT ◀ buttons** to activate or deactivate the **Contrast Plus** feature.

STOP



SMART HELP

Remember: The onscreen menu will disappear in a few seconds after you have finished your adjustment.

Downloaded from www.Manualslib.com manuals search engine

4.2 Перегляд телевізійних програм

Перемикання каналів



1. Натисніть номер (1 - 99) або кнопку **P +/-** на пульті дистанційного керування.
2. Натисніть кнопку **PROGRAM +/-** на бічній панелі телевізора.
3. Натисніть **P⇆P** на пульті дистанційного керування, щоб повернутися до каналу, який переглядали перед тим.

Регулювання гучності



- Натисніть кнопку ◿ + або - на пульті дистанційного керування, чи натисніть **VOLUME** + або - на бічній панелі телевізора.
- Натисніть кнопку 🔇 на пульті дистанційного керування, щоб вимкнути звук. Натисніть кнопку 🔇 ще раз, щоб увімкнути звук.

Примітка. Для навушників:

- Натисніть кнопку ◿ + або - на пульті дистанційного керування, щоб налаштувати рівень гучності навушників.
- Натисніть кнопку 🔇, щоб вимкнути звук гучномовців телевізора.
- Натисніть кнопку ◿ + чи -, щоб знову увімкнути гучномовці телевізора.

4.3 Перегляд зображення з під'єднаних пристроїв

1. Увімкніть пристрій.
2. Натисніть кнопку **SOURCE** на пульті дистанційного керування.



3. За допомогою кнопок ▲ або ▼ виберіть під'єднаний пристрій.
4. Натисніть кнопку **OK**, щоб вибрати пристрій.

UK

Downloaded from www.Manualslib.com manuals search engine

WEIGHING YOUR TRAILER

The diagrams show how to weigh the trailer on scales.

The allowable personal cargo must be distributed in your trailer in such a manner that the Gross Axle Weight Rating is not exceeded.

To determine this, it is necessary to load all of your allowable personal cargo and variable weights. Then hitch the trailer to the tow vehicle with load equalizing hitch properly adjusted as shown on the following pages.

Place the trailer on a scale with both axles only on the scale (see illustration). If the weight on the axles exceeds the axle system G.A.W.R. then some of the personal cargo must be redistributed forward in order to place some of this weight on the tongue.

The tongue weight should be in between 10% - 15% of the trailer's total weight, and must not exceed the tow vehicle's or the hitch's maximum weight rating. To determine tongue load, unhitch tow vehicle and place the tongue hitch post on a scale. The trailer must be properly loaded as determined above, with your allowable personal cargo and variable weights.

Use a scale, such as a bathroom scale, that has a lower weight limit than your tongue load, to check the tongue weight by using the following method (see illustration).

Place a piece of wood of approximately the same thickness as the bathroom scales on the ground in line with the trailer hitch jack as shown. It should be so spaced that a short piece of pipe or other round piece will lay exactly one foot from the centerline of the jack extension.



Place the scales so that another round piece can be exactly two feet from the centerline of the jack extension in the other direction. Place a 4 x 4 on the two round pieces and screw the jack extension down on the top of the 4 x 4 until the tongue of the trailer is supported by it. Multiply the scale reading by three. This will be the tongue weight of your trailer. If you exceed the capacity of the bathroom scales, increase the two-foot dimension to three or four more feet, but always multiply the scale reading by the total number of feet between the wood and scales.

CAUTION: Be sure trailer is level when you read scales.

1. Trailer's Total Weight (cannot exceed GVWR)

2. Trailer's Weight on Axel Assemblies (cannot exceed GVWR)

3. Weight on Trailer's Toungue

Downloaded from www.Manualslib.com manuals search engine

USING THE TIMER

The Timer feature allows you to set the timer to switch to another channel at a specified time while you are watching another channel or when the TV is on standby mode.
Note : For the timer to function, the set must not be switched off. Once the set is switched off, the timer is disabled

Step	Press button		Result on screen
1	MENU	Display the main menu on screen.	
2	∨	Select **Features**.	
3	>	Enter the Features menu	
4	>	Enter Timer menu.	
5	1 2 3 4 5 6 7 8 9 0	Key in the current time starting from the hour follow by minute. This is the time where the "start time" and "stop time" will take reference from.	
6	∨	Select **Start Time**.	
7	1 2 3 4 5 6 7 8 9 0	Key in the time you want the programme to be switched on.	

Downloaded from www.Manualslib.com manuals search engine

Management and Configuration Tools

Compaq offers an extensive set of features and optional tools to support effective server management and configuration. These features are described in this guide:

- SmartStart and Support Software CD
- Fault Tolerance
- Compaq Insight Manager
- Automatic Server Recovery-2 (ASR-2)
- Integrated Management Display (IMD) standard on rack models
- Integrated Management Log
- Integrated Remote Console (IRC)

SmartStart and Support Software

The SmartStart and Support Software CD is the intelligent way to configure your Compaq server with major operating system software. The SmartStart and Support Software CD helps you achieve a well-integrated server that ensures maximum dependability and supportability. For further information about configuration, see Chapter 5, "Server Configuration and Utilities."

The AUTO Lack feature is an integratedcircuit that receives and pracesses data sent by braadcasters, ar ather pragram praviders, that cantain pragram cantent advisaries.When pragrammed by the viewer, a TV with AUTO Lack can respand ta the cantent advisaries and black pragram cantent that may be faund abjectianable (such as affensive language, violence, sexual situatians, etc.). This is a great feature ta censar the type af viewing children may watch.

AUTO Lock offers various BLOCKING controls from which to choose:

Access Code - An Access Code must be set to prevent children from unblocking questionable or censored programming set by their parents.

Block Enable - After an access code has been programmed, you can block programming depending on the received rating and user setting.

Movie Ratings - Certain blocking options exist which will block programming based on ratings patterned by the Motion Pictures Association of America.

TV Ratings - Just like the Movie Ratings, programs can be blocked from viewing using standard TV ratings set by TV broadcasters.

HELPFUL HINT

Remember that 0711 is the default AutoLock code. If your access code has been changed by someone other than you (a child, for example) or you have forgotten the code, you can always get in by inputting the default code.



MOVIE RATINGS

G: General Audience - All ages admitted.
Most parents would find this program suitable for all ages. This type of programming contains little or no violence, no strong language, and little or no sexual dialog or situations.

PG: Parental Guidance Suggested - This programming contains material that parents may find unsuitable for younger children. It may contain one or more of the following moderate violence, some sexual situations, infrequent coarse language or some suggestive dialog.

PG-13: Parents Strongly Cautioned -
This programming contains material that parents may find unsuitable for children under the age of 13. It contains one or more of the following: violence, sexual situations, coarse language, or suggestive dialog.

R: Restricted -This programming is specifically designed for adults. Anyone under the age of 17 should only view this programming with an accompanying
parent or adult guardian. It contains one or more of the following: intense violence, intense sexual situations, strong coarse language, or intensely suggestive dialog.

NC-17: No children under the age of 17 will be admitted - This type of programming should be viewed by adults only. It contains graphic violence, explicit sex, or crude, indecent language.

X: Adults Only - This type of programming contains one or more of the following: very graphic violence, very graphic and explicit or indecent sexual acts, and very coarse and intensely suggestive language.



TV RATINGS

TV-Y All children - Appropriate for all children. Designed for a very young audience, including children ages 2-6. This type of programming is not expected to frighten younger children.

TV-Y7 Directed to Older Children - Designed for children age 7 and above. It may be more appropriate for children who can distinguish between make-believe and reality. This programming may include mild fantasy and comic violence (FV or fantasy violence).

TV-G General Audience - Most parents would find this programming suitable for all ages. This type of programming contains little or no violence, no strong language, and little or no sexual dialog or situations.

TV-PG Parental Guidance Suggested -
Contains material that parents may find unsuitable for younger children. This type of programming contains one or more of the following: Moderate violence (V), some sexual situations (S), infrequent coarse language (L), or some suggestive dialog (D).

TV-14 Parents Strongly Cautioned - Contains some material that many parents would find unsuitable for children under age 14. This type of programming contains one or more of the following: intense violence (V), intense sexual situations (S), strong coarse language (L), or intensely suggestive dialog (D).

TV-MA Mature Audience Only - Specifically designed to be viewed by adults and may be unsuitable for children under 17. This type of programming contains one or more of the following: graphic violence (V), explicit sexual situations (S), or crude, indecent language (L).

Acer Disc-to-Disc Recovery

Restore without a Recovery CD

This recovery process helps you restore the C:\ drive with the original software content that is installed when you purchase your system. Follow the steps below to rebuild your C:\ drive.

Note: The C:\ drive will be reformatted and all data will be erased. It is important to back up all data files before you use this option.

1. Restart the system.
2. While the Acer logo comes out, press <Alt> + <F10> to enter the recovery process.
3. The message **The system has password protection. Please enter 000000:** will be displayed.
4. Enter six zeros and continue.
5. The Acer Recovery main page appears.
6. Use the arrow keys to scroll through the items (operating system versions) and press <Enter> to select.

Multilingual Operating System Installation

Follow the instructions to choose the operating system and language you prefer when you first power on the system.

1. Turn on the system.
2. Acer's multilingual operating system selection menu will pop up automatically.
3. Use the arrow keys to scroll to the language version you want. Press <Enter> to confirm your selection.
4. The operating system and language you choose now will be the only option for future recovery operations.
5. The system will install the operating system and language you choose.

Downloaded from www.Manualslib.com manuals search engine

Figure 1-2 Cluster Member Information from the System Browser Window

Viewing Information about Cluster Resource Groups

1. Click the System Groups button.
2. Select the Cluster tab of the System Browser.

The servers in the cluster are listed in the Cluster Member list. The resource groups are listed in the Cluster Groups list. If the cluster members are configured with the same resources, the Cluster Group list is the same for each cluster member. See Figure 1-2.

Figure 1-3 Cluster Group and Resource Information from the System Browser



The ServerWORKS cluster agent runs on the cluster on which the agent is installed. The NTCMGT MIB defines a variable for DCNT and MSCS resource groups. ServerWORKS Manager Alarm Configuration

Downloaded from www.Manualslib.com manuals search engine

2. Press down the **Menu** button once and then push the **Menu** button to select DEL MUSIC.

3. All of the stored file will be displayed by sequence, switch the **Menu** button to the right or to the left to select Yes to delete the file shown on the Display, or select No to skip to the next file, or select EXIT to leave the current screen.



Delete All Tracks (Files)

1. Press down the **Menu** button once, and then push the **Menu** button to the right four times, and now you should read the message of DELETE FILE appearing on the Display.

2. Press down the **Menu** button once and then push the **Menu** button to the right twice to select DEL ALL MUSIC.

Downloaded from www.Manualslib.com manuals search engine

without network authentication.

Encryption ~ WEP: you decide to setup the basic data encryption with a defined network key.

■ **Shared Key + WEP**

You decide to apply both authentication and data encryption to prevent unauthouized login.

■ **WPA-PSK + TKIP**

The most advanced authentication and data encryption that provide the best security protection.

7.4. ASCII/ PASSPHRASE

The most advanced authentication and data encryption that provide the best security protection.

■ ASCII: You should provide either 5 or 13 ASCII characters on Network key edit box.

■ PASSPHRASE: You could input words on Network Key edit box.

64 bits: The generated pass key is 64-bit to be complied with data packets.

128 bits: The generated pass key is 128-bit to be complied with data packets.

■ Hexadecimal: While both ASCII and PASSPHRASE are not checked, you should input hexadecimal number in the network key box. For example, 10 digits hex number for 64-bit WEP or 26 digits hex number for 128-bit WEP.

7.5. Key index (1 ~4)

At most four key index to represent the opposite network key.

B. Advanced Page

Users could setup the advanced characteristics of network packet for transmission on this page.

Downloaded from www.Manualslib.com manuals search engine

Management (Computer / Video Mode)

Lamp Mode

- ECO : Selecting "ECO" mode to dim the projector Lamp, which lower power consumption, will extend the lamp life and reduce noise.
- Standard : Apply " Standard " mode to reurn normal operation.
- Enhanced : Choosing "Enhanced " mode will brighten the projector Lamp to get a brighter screen.

Menu Location

Choose the Menu location on the display screen.

Projection

- **Front-Desktop**

  The factory default setting.

- **Rear-Desktop**

  When you select this function, the projector reverses the image so you can project behind a translucent screen.

- **Front-Ceiling**

  When you select this function, the projector turns the image upside down for ceiling-mounted projection.

- **Rear-Ceiling**

  When you select this function, the projector reverses and turns the image upside down at same time. You can project from behind a translucent screen with ceiling mounted projection.

Downloaded from www.Manualslib.com manuals search engine

OPERACIONES

A. Desbloqueo del código de usuario
Cuando el código de usuario registrado se introduce a través del teclado (entre 4 y 6 dígitos), el LED (grupo 1: naranja, grupo 2: verde) se enciende, el zumbador suena y la cerradura eléctrica se desbloquea.
ej.): grupo 1 grupo 2
1006 04B2

- El intervalo de tiempo durante el que se debe pulsar el botón es de aproximadamente 10 segundos. Si el intervalo de tiempo excede aproximadamente 10 segundos, el valor de entrada se borra.
- Si se equivoca al introducir el código de usuario, repita la operación.
- Cuando se ha configurado la función de "Bloqueo", la función de liberación se bloquea y la operación entrada se inhabilita durante un tiempo especificado (10 ~ 99 segundos) si se introducen códigos no válidos un número de veces configurado (10 ~ 99 veces). (Referencia: "Bloqueo".) Durante este intervalo de tiempo, las teclas parpadean 4 veces, el LED (naranja) parpadea durante el tiempo de desactivación configurado y el zumbador suenan durante aproximadamente 3 segundos.

B. Desbloqueo conectado al temporizador
Cuando la función de desbloqueo conectado al temporizador está activada, la puerta se puede desbloquear pulsando la tecla (0) durante el tiempo establecido mientras que el temporizador esté conectado. El encendido de la tecla (0) se activa mientras el temporizador ha activado éste durante la configuración.

C. Desbloqueo utilizando el botón de solicitud de salida/entrada
Cuando salga, puede activar la cerradura eléctrica pulsando el botón de solicitud de salida/entrada conectado a la unidad. Cuando se pulsa el botón de solicitud de salida/entrada 1, se libera el relé 1 y cuando se pulsa el botón de solicitud de salida/entrada 2, se libera el relé 2.
- Cuando se desbloquee a la puerta utilizando el botón de solicitud de salida/entrada, el LED no se enciende y el zumbador no suena.

PRECAUCIONES TÉCNICAS

- Temperatura de operación : Entre -20°C y 60°C (-4˚F to 140˚F)
- Limpieza: Limpie la unidad con un paño suave humedecido con un producto de limpieza neutro. No utilice limpiadores ni paños abrasivos.
- La unidad es resistente a la intemperie. Sin embargo, no debe rociar agua a alta presión directamente en el teclado del control de acceso. Demasiada humedad puede causar problemas a la unidad.
- Presione y suelte las teclas (7),(0),(8), y (#) simultáneamente cuando la unidad no esté funcionando. ※)Los LEDs (naranja y verde) parpadean, el zumbador suena y se efectúa el reinicio. (Con esto no se configuran los valores predeterminados.)
- Si el reinicio no funciona, contacte el técnico que montó la unidad.

ESPECIFICACIONES

- Alimentación : 12 - 24V CA
  12 - 24V CC
- Consumo: CC: Máx. 70mA
  CA: Máx. 100mA
- Dimensiones:
  AC-10S: 125(H) × 98(A) × 33(P)mm
  AC-10F: 132(H) × 117(A) × 5(P)(entrante: 29)mm
  Caja interna para el montaje empotrado: 100(H) × 85(A) × 45(P)mm
- Peso: AC-10S: aprox. 600g
  AC-10F: aprox. 670g
- IP: IP54
- Número de circuitos de relé: 2
- Contacto de relé: N/O, N/C
- Capacidad de los contactos de relé: 24V CC, 3A (carga resistiva)
  1A (carga inductiva)
  24V CA, 3A (carga resistiva)
  1A (carga inductiva)

GARANTÍA

Aiphone garantiza que sus productos están libres de defectos de material y mano de obra, en uso y mantención normal, por un período de dos años despues de la entrega final al último usuario y reparará sin costo, o reemplazará sin cargo, si llegara a resultar defectuoso, mediante una inspección que determine que efectivamente está con defecto y en garantía. Aiphone se reserva para sí la facultad única de tomar la decisión final sobre si existe una falla en materiales y/o mano de obra, y si acaso el producto está o no cubierto dentro de la garantía. Esta garantía no se aplicará a ningún producto Aiphone que haya sido sometido a maltrato,negligencia,a ccidente, o usado de manera diferente a las instrucciones proporcionadas, o bien a unidades las cuales hayan sido arregladas o alteradas fuera de fábrica. Esta garantía no ampara baterías o el deterioro causado por baterías usadas en conjunto con el producto. La garantía cubre solo las reparaciones efectuadas en el mesón de trabajo y cualquier reparación debe ser efectuada en el taller o lugar designado por escrito por Aiphone. Aiphone no se responsabilizará por costos incurridos en cualquier llamada de servicio al sitio mismo en que se presente el defecto. Aiphone no indemnizará por ninguna pérdida o daño en que se incurra debido a la avería o falla de sus productos durante su uso, ni por ningún inconveniente o pérdida que se produzca como consecuencia.

Downloaded from www.Manualslib.com manuals search engine

To record

Video recorder and TV set only linked by aerial cables

- Select the channel number you wish to record on the videorecorder.
- Press the videorecorder record key.

In this case, you can record a program on a channel while watching another program on another channel.

Video recorder and TV set only linked with a Eurocable

- Select the channel number on your TV set.
- Select the socket corresponding to the connection with the TV on the videorecorder (usually **EXT**).
- Press the video recorder record key.



In case of a problem, refer to the operating manual of your video recorder.

In this case, the recorded program will be that of the selected TV channel.

Using your Video recorder with the TV remote control

The TV set's remote control enables you to use some of the audio and video equipment which makes up our product range.

To use this remote control, proceed as follows :

- Lift the remote control flap.
- Press simultaneously the VCR key and one of the following keys to:



Ⓐ : Record a program.

Ⓑ : Rewind a cassette, without display.

Ⓒ : Wind a cassette, without display.

Ⓓ : Stop a cassette.

Ⓔ : Play back a cassette.

Downloaded from www.Manualslib.com manuals search engine

REPLACEMENT PARTS

Remote Control	136-4840

SPECIFICATIONS

LCD Backlighting	Edge Light Tube
Resolution	1440 x 234
Pixels	336, 960
Operation Temperature	32 ~131° F (0 ~ 55° C)
Storage Temperature	-4 ~ 158° F (-20 ~ 70° C)
Backlit life	10,000 Hours
Video Display System	NTSC / PAL
Headphone Audio Output	0.03W @ 32 ohms
Video Output	1.0Vp-p @ 75 ohms
Power Source	12V DC
Dimension	L x W x H
	11.0" x 9.5" x 1.7"
	289mm x 243mm x 44mm

Specifications subject to change without notice.

Downloaded from www.Manualslib.com manuals search engine

Management (Computer / Video Mode)

Acer eOpening Management is a PC utility for user to change the default start-up screen of Acer projector to their desired image. You can install *Acer eOpening Management* from the bundled CD. Connect the projector to your PC with the bundled USB cable then execute *Acer eOpening Management* utility to download your desired image from your PC to projector.

Before the download starts, the projector must enter "Download Mode" first. Please follow the instruction below to enter "Download Mode".

1. If the AC power cord of the projector was unplugged, plug the AC power.
2. Powering On the Projector
3. Please make sure the USB cable has been plugged and connected to your projector.

Downloaded from www.Manualslib.com manuals search engine

Play Store

Tap **Play Store** from the *Home* screen or *Application* menu to open *Google Play*. Here you can obtain a variety of add-on programs and APPs to enhance the functionality of your tablet.



You can browse Google Play by category or tap the search icon to search for a specific application.

For the best user experience, you are advised to not download APPs that use 3D graphics.

Once you have selected an application, tap the **Install** button to download and install the application. You will be told which services (contact information, wireless access, GPS, etc.) the application

Downloaded from www.Manualslib.com manuals search engine

	Use an opening tool to disconnect the LCM FPC from the main board.
	Remove the Mylar from the main FPC connector.
	Use an opening tool to disconnect the TP FPC.

Downloaded from www.Manualslib.com manuals search engine